



EC DECLARATION OF PERFORMANCE

Company: SIA RUBRIG
Rīgas gatve 8, Ādaži
LV 2164, Latvija

Product: Rubslice Multi tiles with 3mm Rubslice wear layer

Description: resilient rubber flooring for indoor fitness

Material: wear layer Rubslice 930 black SBR
wear layer Rubslice 1050 85% black SBR + 15% virgin EPDM
wear layer Rubslice 1300 100% virgin EPDM
bottom recycled black SBR granules, MDI binder

Specification: Annex to ZA.4 to EN14041-2004

Testing institutes:

Eurofins Product Testing A/S, Smedeskovvej 38, 8464 Galten, Denmark

Pavus, a.s., Prosecka 412/74, 19000 Praha-9, Czech Republic

Technical Test Institute for Construction Prague, Zahradni 15, 32600 Plzen, Czech Republic

ISP GmbH Institut für Sportstättenprüfung, Süd Strasse 1a, 49196 Bad Laer, Vācija

SIA R & D akustika, Kurzemes prospekts, Rīga, LV-1067, Latvija

Declared performance

Flammability rating with Rubslice 930 and Rubslice 1050	$E_{fl} - s1$	EN 13501-1
Flammability rating with Rubslice 1300	$D_{fl} - s1$	EN 13501-1
Emission of formaldehyde	pass	AgBB
Dimensions/tolerances +/- 2mm	500x1000, 1000x1000mm	
Thickness/tolerances +/-2mm	20, 25, 30, 40mm	
Approx. weight, m2	20mm 18.0 kg 25mm 22.5 kg 30mm 25.8 kg 40mm 30.5 kg	
Density wear layer RS930	930 kg/m ³	
Density wear layer RS1050	1050 kg/m ³	
Density wear layer RS1300	1250 kg/m ³	
Density base	900 kg/m ³	
Impact sound insulation	25mm 25dB 30mm 26dB 40mm 30dB	ISO 10140-3
Force reduction	25mm 52% 30mm 52% 40mm 61%	EN 14094
Impact resistance	No damage	EN 14094

Standard vertical deformation	25mm 2.3% 30mm 1.9% 40mm 3.5%	EN 14094
Slip resistance under wet conditions	C (24°) high slip resistance	DIN 51097

CE marking according to EN 14041-2005

The declaration of performance is issued under the sole responsibility of the manufacturer identified above.

Ādaži, 01.06.2021



Gundars Brants
Export Manager